

Vertical Grinders

Cleco[®]



NEW Cleco® Vertical Grinders

For applications requiring **maximum material removal**, The New Cleco® Vertical Grinder is the solution.

Engineered for heavy-use industrial applications, this product is built to deliver unmatched productivity and maximum material removal.

The Cleco Vertical Grinder is ideally suited for all environments of heavy metal fabrication.

QUALITY

The Cleco® Vertical Grinders are engineered for maximum reliability. All products are 100% tested to ensure the highest quality.

Cleco Vertical Grinders require less maintenance and have more user "up time" to ensure the most from your investment.

POWER

3HP (2.3Kw) or 4HP (3.1Kw) vane motor are engineered for maximum sustained power.

Cleco Vertical Grinders provide maximum power to generate maximum material removal.

DURABILITY

Streamlined one piece all metal housing and handles are engineered for ultimate ruggedness.

Cleco Vertical Grinders can withstand the most abusive environments.

SAFETY

All Cleco Vertical Grinders come standard with safety lock throttle lever, industrial governor, and ANSI compliant guards.

Safety is of the utmost importance in any work environment. Cleco Vertical Grinders meet the highest safety standards.

VERSATILITY

Reversible Throttle Handle and Interchangeable 6" (150mm), 7" (180mm), and 9" (230mm) guards.

Cleco Vertical Grinders can be easily and quickly configured for a variety of user preferences and applications.

ERGONOMICS

Reduced weight by up to 1.7 lbs (0.7 Kg) and reduced height by almost 1" (25mm).

Improved ergonomics with Cleco Vertical Grinders enable a more efficient usage and higher operator productivity.



PRODUCT SPECIFICATIONS



MODEL	EXTERNAL THREAD	ABRASIVE CAPACITY	MAX. FREE SPEED	POWER		HEIGHT		WEIGHT		AIR INLET
			rpm	hp	Kw	in	mm	lbs	kg	
3 HP (2.3Kw) SERIES										
3060AVL-06	5/8" 11 External Thread	6" (150mm) Type 11	6,000	3.1	2.3	6.9	175.3	10.2	4.6	1/2"
3060AVL-07	5/8" 11 External Thread	7" (180mm) Type 27	6,000	3.1	2.3	6.9	175.3	9.7	4.4	1/2"
3060AVL-09	5/8" 11 External Thread	9" (230mm) Type 27	6,000	3.1	2.3	6.9	175.3	10.4	4.7	1/2"
4 HP (3.1Kw) SERIES										
4060AVL-06	5/8" 11 External Thread	6" (150mm) Type 11	6,000	4.1	3.1	8.2	207.9	11.6	5.3	1/2"
4060AVL-07	5/8" 11 External Thread	7" (180mm) Type 27	6,000	4.1	3.1	8.2	207.9	11.1	5.0	1/2"
4060AVL-09	5/8" 11 External Thread	9" (230mm) Type 27	6,000	4.1	3.1	8.2	207.9	11.8	5.4	1/2"

**3HP
(2.3Kw)**



**4HP
(3.1Kw)**



**GUARD
Options**



6" (150mm)

7" (180mm)

9" (230mm)

